

EMC Test Report

Client Name : **Shenzhen JHC Technology Development Co., LTD**

Client Address : **B Area, 3rd floor, A Block Junxiangda Building, N0.9 Zhongshanyuan Road, Nanshan Distr., Shenzhen, China**

Product Name : **Industrial Embedded Computer**

Report Date : **Oct. 11, 2022**

Shenzhen Anbotech Compliance Laboratory Limited



Contents

1. General Information	5
1.1. Client Information	5
1.2. Description of Device (EUT)	5
1.3. Auxiliary Equipment Used During Test	6
1.4. Description of Test Mode	7
1.5. Test Summary	7
1.6. Test Equipment List	8
1.7. Description of Test Facility	11
1.8. EMS Performance Criteria	12
2. Power Line Conducted Emission Test	13
2.1. Test Standard and Limit	13
2.2. Test Setup	13
2.3. Test Procedure	14
2.4. Test Results	14
3. Asymmetric Mode Conducted Emission at Telecom Port	17
3.1. Test Standard and Limit	17
3.2. Test Setup	17
3.3. Test Procedure	18
3.4. Test Results	18
4. Radiated Emission Test (Below 1 GHz)	20
4.1. Test Standard and Limit	20
4.2. Test Setup	20
4.3. Test Procedure	21
4.4. Test Results	21
5. Radiated Emission Test (Above 1GHz)	24
5.1. Test Standard and Limit	24
5.2. Test Setup	24
5.3. Test Procedure	25
5.4. Test Results	25
6. Harmonic Current Test	28
6.1. Test Standard	28
6.2. Test Setup	28
6.3. Test Procedure	28
6.4. Test Results	28
7. Voltage Fluctuations & Flicker Test	29
7.1. Test Standard	29
7.2. Test Setup	29
7.3. Test Procedure	29
7.4. Test Results	29



8. Electrostatic Discharge Immunity Test	31
8.1. Test Specification	31
8.2. Test Setup	31
8.3. Test Procedure	31
8.4. Test Results	32
9. RF Field Strength Immunity Test	34
9.1. Test Specification	34
9.2. Test Setup	34
9.3. Test Procedure	35
9.4. Test Results	35
10. Electrical Fast Transient/Burst Immunity Test	37
10.1. Test Specification	37
10.2. Test Setup	37
10.3. Test Procedure	38
10.4. Test Results	38
11. Surge Immunity Test	40
11.1. Test Specification	40
11.2. Test Setup	40
11.3. Test Procedure	40
11.4. Test Results	40
12. Injected Currents Susceptibility Test	42
12.1. Test Specification	42
12.2. Test Setup	42
12.3. Test Procedure	43
12.4. Test Results	43
13. Power Frequency Magnetic Field Immunity Test	45
13.1. Test Specification	45
13.2. Test Setup	45
13.3. Test Procedure	45
13.4. Test Results	45
14. Voltage Dips and Interruptions Immunity Test	46
14.1. Test Specification	46
14.2. Test Setup	46
14.3. Test Procedure	46
14.4. Test Results	46
APPENDIX I -- TEST SETUP PHOTOGRAPH	48
APPENDIX II -- EXTERNAL PHOTOGRAPH	54
APPENDIX III -- INTERNAL PHOTOGRAPH	57



TEST REPORT

Applicant : Shenzhen JHC Technology Development Co., LTD

Manufacturer : Shenzhen JHC Technology Development Co., LTD

Product Name : Industrial Embedded Computer

Test Model No. : KMDA-2630-T001

Reference Model No. : KMDA-2630-T002, KMDA-2630-T003, KMDA-2630-T004,
KMDA-2630-S001, KMDA-2630-S002, KMDA-2630-S003,
KMDA-2630-S004

Trade Mark : JHCTECH

Rating(s) : Input: DC 12.0V 1.51A 18.12W

Test Standard(s) : **EN 55032: 2015+A1:2020;**
EN IEC 61000-3-2: 2019/A1:2021;
EN 61000-3-3: 2013+A1:2019+A2:2021;
EN 55035: 2017+A11:2020;
(IEC 61000-4-2; IEC 61000-4-3; IEC 61000-4-4;
IEC 61000-4-5; IEC 61000-4-6; IEC 61000-4-8; IEC 61000-4-11)

The device described above is tested by Shenzhen Anbotech Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotech Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the EN 55032, EN IEC 61000-3-2, EN 61000-3-3, EN 55035 requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotech Compliance Laboratory Limited.

Date of Receipt: Aug. 04, 2022

Date of Test: Aug. 04~Sept. 07, 2022

Prepared By:

We Zeng

(We Zeng)

Approved & Authorized Signer:

KingKongJin

(KingKong Jin)



1. General Information

1.1. Client Information

Applicant	:	Shenzhen JHC Technology Development Co., LTD
Address	:	B Area, 3rd floor, A Block Junxiangda Building, N0.9 Zhongshanyuan Road, Nanshan Distr., Shenzhen, China
Manufacturer	:	Shenzhen JHC Technology Development Co., LTD
Address	:	B Area, 3rd floor, A Block Junxiangda Building, N0.9 Zhongshanyuan Road, Nanshan Distr., Shenzhen, China
Factory	:	Shenzhen JHC Technology Development Co., LTD
Address	:	B Area, 3rd floor, A Block Junxiangda Building, N0.9 Zhongshanyuan Road, Nanshan Distr., Shenzhen, China

1.2. Description of Device (EUT)

Product Name	:	Industrial Embedded Computer
Test Model No.	:	KMDA-2630-T001
Reference Model No.	:	KMDA-2630-T002, KMDA-2630-T003, KMDA-2630-T004, KMDA-2630-S001, KMDA-2630-S002, KMDA-2630-S003, KMDA-2630-S004 (Note: All samples are the same except the model number & appearance, so we prepare "KMDA-2630-T001" for test only.)
Trade Mark	:	JHCTECH
Test Power Supply	:	AC 230V, 50Hz
Test Sample No.	:	1-1-1
Product Description	:	Adapter 1 MODEL: KPL-060F-VI INPUT: 100-240V~ 50/60Hz 1.7A OUTPUT: +12.0V --- 5.0A 60.0W
	:	Adapter 2 MODEL NO.: FSP060-DBAB1 INPUT: 100-240V~, 1.5A, 50-60Hz OUTPUT: 12.0V --- 5.0A MAX (60W MAX)

Remark: (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.



1.3. Auxiliary Equipment Used During Test


MONITOR1	:	Manufacturer: PHILIPS
	:	M/N: 273V7QDSBF/93 S/N: UK0A2120004629A2K Input: AC100-240~50/60Hz 1.6A
MONITOR2	:	Manufacturer: AOC
	:	M/N: LV273HUPR S/N: APM79A00124 7Q Input: 100-240~50/60Hz 1.5A
KEYBOARD	:	Manufacturer: DELL
	:	M/N: SK-8120 S/N: CN-0DJ365-71616-49J-0MVR-A00 Input Rating: DC 5V, 0.05A CE, FCC, VCCI, KCC, TUV-GS Cable: 1.8m, unshielded
MOUSE	:	Manufacturer: DELL
	:	M/N: MS111-T S/N: CN-0KW2YH-71616-488-1CBJ Input Rating: DC 5V, 0.1A Cable: 1.8m, unshielded CE, FCC, VCCI, KCC, TUV-GS



1.4. Description of Test Mode

Pretest Mode	Description
Mode 1	On

For Mode 1 Block Diagram of Test Setup



1.5. Test Summary

Test Items	Test Mode	Status
Power Line Conducted Emission Test	Mode 1	P
Asymmetric Mode Conducted Emission at Telecom Port	Mode 1	P
Radiated Emission Test (Below 1 GHz)	Mode 1	P
Radiated Emission Test (Above 1GHz)	Mode 1	P
Harmonic Current Test	/	N
Voltage Fluctuations & Flicker Test	Mode 1	P
Electrostatic Discharge Immunity Test	Mode 1	P
RF Field Strength Immunity Test	Mode 1	P
Electrical Fast Transient/Burst Immunity Test	Mode 1	P
Surge Immunity Test	Mode 1	P
Injected Currents Susceptibility Test	Mode 1	P
Power frequency Magnetic Field Immunity Test	/	N
Voltage Dips and Interruptions Immunity Test	Mode 1	P
P) Indicates "PASS". F) Indicates "Fail". N) Indicates "Not applicable".		



1.6. Test Equipment List☒ Power Line Conducted Emission Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Oct. 22, 2021	1 Year
2.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040D T001	Jul. 05, 2022	1 Year
3.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 22, 2021	1 Year
4.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2021	1 Year
5.	Software Name EZ-EMC	Ferrari Technology	ANB-03A	N/A	N/A	N/A

☒ Asymmetric Mode Conducted Emission at Telecom Port

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	ISN	Schwarzbeck	NTFM 8158	#172	Oct. 22, 2021	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Oct. 22, 2021	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Oct. 22, 2021	1 Year
4.	Software Name EZ-EMC	Ferrari Technology	ANB-03A	N/A	N/A	N/A
5.	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040D T001	Jul 05, 2022	1 Year

☒ Radiated Emission Test (Below 1 GHz)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 22, 2021	1 Year
2.	Pre-amplifier	SONOMA	310N	186860	Oct. 22, 2021	1 Year
3.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 22, 2021	2 Year
4.	Software Name EZ-EMC	Ferrari Technology	ANB-03A	N/A	N/A	N/A



☒ Radiated Emission Test (Above 1GHz)

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	Oct. 22, 2021	1 Year
2.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Oct. 22, 2021	2 Year
3.	Pre-amplifier	SONOMA	310N	186860	Oct. 22, 2021	1 Year
4.	Software Name EZ-EMC	Ferrari Technology	ANB-03A	N/A	N/A	N/A
5.	Preamplifier	SKET Electronic	BK1G18G30 D	KD17503	Oct. 22, 2021	1 Year
6.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Oct. 22, 2021	2 Year

☒ Harmonic Current and Flicker Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Programmable AC Power source	IVYTECH	APS-5005A	632734	Oct. 22, 2021	1 Year
2.	Harmonic and Flicker Analyzer	EMC-PARTNER	HMONICS 1000-1P	164	Oct. 22, 2021	1 Year
3.	Harmonics-1000	N/A	Ed.3.0+4.0	N.A	N/A	N/A

☒ Electrostatic Discharge Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	ESD Simulators	emtest	ESD NX30.1	11936	Mar. 25, 2022	1 Year

☒ RF Field Strength Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Signal Generator	Agilent	N5182A	MY48180656	Oct. 22, 2021	1 Year
2.	Amplifier	Micotoop	MPA-80-100 0-250	MPA1903096	Oct. 22, 2021	1 Year
3.	Amplifier	Micotoop	MPA-1000-6 000-100	MPA1903122	Oct. 22, 2021	1 Year
4.	Log-Periodic Antenna	Schwarzbeck	VULP9118E	00992	N/A	N/A
5.	Horn Antenna	Instruments corporation	GTH-0118	351600	Oct. 22, 2021	2 Year
6.	Power Sensor	Agilent	E9301A	MY41498906	Oct. 22, 2021	1 Year
7.	Power Sensor	Agilent	E9301A	MY41498088	Oct. 22, 2021	1 Year
8.	Power Meter	Agilent	E4419B	GB40202909	Oct. 22, 2021	1 Year
9.	Electric field Probe	Narda	EP 601	811ZX10351	Oct. 22, 2021	1 Year
10.	RS Test software	EMtrace	EM 3	V1.1.7	N/A	N/A



☒ Electrical Fast Transient/Burst Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Surge Generator	TESEQ	NSG 3060	1480	Oct. 22, 2021	1 Year
2.	CDN	TESEQ	CDN 3061	1408	Oct. 22, 2021	1 Year
3.	EFT-Clamp	PRIMA	EFT-Clamp	/	Oct. 22, 2021	1 Year

☒ Surge Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Surge Generator	TESEQ	NSG 3060	1480	Oct. 22, 2021	1 Year
2.	CDN	TESEQ	CDN 3061	1408	Oct. 22, 2021	1 Year
3.	Telecom port surge generator	PMI	TW101	190411	May 13, 2022	1 Year

☒ Injected Currents Susceptibility Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	C/S Conducted Immunity Test System	FRANKONIA	CIT-10	126A1196/2012	Oct. 22, 2021	1 Year
2.	CDN	FRANKONIA	CDN - M2+ M3	A2210178/2012	Oct. 22, 2021	1 Year
3.	6dB Attenuator	FRANKONIA	DAM 26W	1172202	Oct. 22, 2021	1 Year
4.	CIT-10	FRANKONIA	Version1.1.7	N/A	N/A	N/A
5.	EM-Clamp	FRANKONIA	EMCL-20	18101728-0103	May 17, 2022	1 Year

☐ Power frequency Magnetic Field Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Power Frequency Magnetic Field Generator	EVERFINE	EMS61000-8K	906002	Oct. 22, 2021	1 Year

☒ Voltage Dips and Interruptions Immunity Test

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	CYCLE SAG Simulator	PRIMA	DRP61011A G	PR12046234	Oct. 22, 2021	1 Year



1.7. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111.

ISED-Registration No.: 8058A

Shenzhen Anbotech Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotech Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518128



1.8. EMS Performance Criteria**Performance criterion A**

The equipment shall continue to operate as intended without operator intervention. No degradation of performance, loss of function or change of operating state is allowed below a performance level specified by the manufacturer when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance. If the minimum performance level or the permissible performance loss is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Performance criterion B

During the application of the disturbance, degradation of performance is allowed. However, no unintended change of actual operating state or stored data is allowed to persist after the test.

After the test, the equipment shall continue to operate as intended without operator intervention; no degradation of performance or loss of function is allowed, below a performance level specified by the manufacturer, when the equipment is used as intended. The performance level may be replaced by a permissible loss of performance.

If the minimum performance level (or the permissible performance loss), or recovery time, is not specified by the manufacturer, then either of these may be derived from the product description and documentation, and by what the user may reasonably expect from the equipment if used as intended.

Performance criterion C

Loss of function is allowed, provided the function is self-recoverable, or can be restored by the operation of the controls by the user in accordance with the manufacturer's instructions. A reboot or re-start operation is allowed.

Information stored in non-volatile memory, or protected by a battery backup, shall not be lost.



2. Power Line Conducted Emission Test

2.1. Test Standard and Limit

Test Standard:	EN 55032
----------------	----------

☒ Limits for conducted emission at the AC mains power ports of Class A equipment

Frequency (MHz)	Limits (dB μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	79.0	66.0
0.50 ~ 30.00	73.0	60.0

Remark: The lower limit shall apply at the transition frequencies.

☐ Limits for conducted emission at the AC mains power ports of Class B equipment


Frequency (MHz)	Limits (dB μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	66.0 ~ 56.0 *	56.0 ~ 46.0 *
0.50 ~ 5.00	56.0	46.0
5.00 ~ 30.00	60.0	50.0

Remark:

(1) The lower limit shall apply at the transition frequencies.

(2) The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

2.2. Test Setup



2.3. Test Procedure

The table-top EUT is placed on a non-conductive table 0.8 m above the horizontal ground reference plane, and the back of the EUT is 0.4 m away from the vertical ground reference plane, and at least 0.8 m from any other metal surface or ground plane. The floor-standing EUT is placed on an insulating support 0.1 m above the horizontal ground reference plate, at least 0.8 m away from other metal objects.

Connect EUT to the power mains through an LISN. Where the mains cable supplied by the manufacturer is longer than 1 m, the excess should be folded at the center into a bundle no longer than 0.4 m, so that its length is shortened to 1 m. All the peripherals are connecting to the other LISN.

The initial testing identified the frequency that has the highest disturbance relative to the limit while operating the EUT in typical modes of operation and cable positions in a test setup representative of typical system configuration.

The identification of the frequency of highest disturbance with respect to the limit was found by investigating disturbances at a number of significant frequencies. The probable frequency of maximum disturbance had been found and that the associated cable and EUT configuration and mode of operation had been identified.

Set the test-receiver to quasi peak detect function and average detect function, and to measure the conducted emissions values.

2.4. Test Results


PASS

The test curves are shown in the following pages.



Power Line Conducted Test Data

Test Site: 1# Shielded Room
Test Specification: AC 230V, 50Hz
Comment: Live Line
Temp.: 22.8°C Hum.: 48%




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1539	36.74	9.70	46.44	79.00	-32.56	QP	
2	0.1860	37.48	9.71	47.19	79.00	-31.81	QP	
3	0.2420	33.66	9.71	43.37	79.00	-35.63	QP	
4	0.2420	30.06	9.71	39.77	66.00	-26.23	AVG	
5	0.3060	35.08	9.73	44.81	79.00	-34.19	QP	
6	0.3060	33.01	9.73	42.74	66.00	-23.26	AVG	
7	7.1380	19.97	9.78	29.75	60.00	-30.25	AVG	
8	7.2620	19.97	9.79	29.76	60.00	-30.24	AVG	
9	12.0980	36.21	9.90	46.11	73.00	-26.89	QP	
10	12.0980	27.77	9.90	37.67	60.00	-22.33	AVG	
11	17.5100	36.68	10.06	46.74	73.00	-26.26	QP	
12	17.8140	29.70	10.07	39.77	60.00	-20.23	AVG	

Note: Result = Reading + Factor Over Limit = Result - Limit



Power Line Conducted Test Data

Test Site: 1# Shielded Room
Test Specification: AC 230V, 50Hz
Comment: Neutral Line
Temp.: 22.8°C Hum.: 48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1580	37.84	9.70	47.54	79.00	-31.46	QP	
2	0.2020	32.72	9.71	42.43	79.00	-36.57	QP	
3	0.2460	30.42	9.71	40.13	66.00	-25.87	AVG	
4	0.3060	31.97	9.73	41.70	79.00	-37.30	QP	
5	0.3060	31.32	9.73	41.05	66.00	-24.95	AVG	
6	9.3100	24.02	9.82	33.84	60.00	-26.16	AVG	
7	9.4300	31.99	9.82	41.81	73.00	-31.19	QP	
8	11.9780	27.95	9.89	37.84	60.00	-22.16	AVG	
9	12.2739	36.70	9.90	46.60	73.00	-26.40	QP	
10	14.1540	23.41	9.96	33.37	60.00	-26.63	AVG	
11	17.4500	34.16	10.05	44.21	73.00	-28.79	QP	
12	17.8779	27.42	10.07	37.49	60.00	-22.51	AVG	

Note: Result = Reading + Factor Over Limit = Result - Limit



3. Asymmetric Mode Conducted Emission at Telecom Port

3.1. Test Standard and Limit

Test Standard	EN 55032
---------------	----------

☒ Limits for asymmetric mode conducted emissions of Class A equipment

Frequency (MHz)	Limits (dB μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	97.0 ~ 87.0 *	87.0 ~ 74.0 *
0.50 ~ 30.00	87.0	74.0

Remark:

The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.


☐ Limits for asymmetric mode conducted emissions of Class B equipment

Frequency (MHz)	Limits (dB μ V)	
	Quasi-peak Level	Average Level
0.15 ~ 0.50	84.0 ~ 74.0 *	74.0 ~ 44.0 *
0.50 ~ 30.00	74.0	64.0

Remark:

The limit decreases linearly with the logarithm of the frequency in the range 0.15MHz to 0.50MHz.

3.2. Test Setup



3.3. Test Procedure

The table-top EUT is placed on a non-conductive table 0.8 m above the horizontal ground reference plane, and the back of the EUT is 0.4 m away from the vertical ground reference plane, and at least 0.8 m from any other metal surface or ground plane. The floor-standing EUT is placed on an insulating support 0.1 m above the horizontal ground reference plane, at least 0.8 m away from other metal objects.

Connect EUT to the power mains through an LISN. Where the mains cable supplied by the manufacturer is longer than 1 m, the excess should be folded at the center into a bundle no longer than 0.4 m, so that its length is shortened to 1 m. All the peripherals are connecting to the other LISN.

The EUT was connected to the peripheral equipment through the ISN and linked in normal condition.

Set the test-receiver to quasi peak detect function and average detect function, and to measure the asymmetric mode conducted emission values.

3.4. Test Results


PASS

The test curves are shown in the following pages.



Asymmetric Mode Conducted Emission Test Data

Test Site: 1# Shielded Room
Test Specification: AC 230V, 50Hz
Comment: Telecom Port
Temp.: 22.8°C Hum.: 48%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.6780	31.80	19.13	50.93	74.00	-23.07	AVG	
2	0.8180	41.98	19.12	61.10	87.00	-25.90	QP	
3	0.8180	34.67	19.12	53.79	74.00	-20.21	AVG	
4	1.1580	37.00	19.11	56.11	87.00	-30.89	QP	
5	1.6300	41.09	19.11	60.20	87.00	-26.80	QP	
6	1.6300	37.55	19.11	56.66	74.00	-17.34	AVG	
7	1.9540	38.03	19.11	57.14	87.00	-29.86	QP	
8	2.4460	41.19	19.11	60.30	87.00	-26.70	QP	
9	2.4460	34.89	19.11	54.00	74.00	-20.00	AVG	
10	3.6260	30.14	19.14	49.28	74.00	-24.72	AVG	
11	17.8940	29.77	19.47	49.24	74.00	-24.76	AVG	
12	22.9260	35.36	19.59	54.95	87.00	-32.05	QP	

Note: Result = Reading + Factor Over Limit = Result - Limit



4. Radiated Emission Test (Below 1 GHz)

4.1. Test Standard and Limit

Test Standard	EN 55032
---------------	----------

☒ Limit for radiated emissions at frequencies up to 1 GHz for class A equipment

Frequency (MHz)	Distance (Meters)	Field Strengths Limit (dB μ V/m)
30 ~ 230	3	50
230 ~ 1000	3	57


Remark: The lower limit shall apply at the transition frequencies.

☐ Limit for radiated emissions at frequencies up to 1 GHz for class B equipment

Frequency (MHz)	Distance (Meters)	Field Strengths Limit (dB μ V/m)
30 ~ 230	3	40
230 ~ 1000	3	47

Remark: The lower limit shall apply at the transition frequencies.

4.2. Test Setup



4.3. Test Procedure

The table-top EUT is placed on a non-conductive table 0.8 m above the horizontal ground reference plane. The floor-standing EUT is placed on an insulating support 0.1 m above the horizontal ground reference plane.

The EUT was set 3 m away from the receiving antenna that was mounted on a non-conductive mast. The antenna can move up and down between 1 to 4 m to find out the maximum emission level.

The turntable can rotate 360 degree to determine the position of the maximum emission level.

The initial testing identified the frequency that has the highest disturbance relative to the limit while operating the EUT in typical modes of operation and cable positions in a test setup representative of typical system configuration.

The identification of the frequency of highest emission with respect to the limit was found by investigating emissions at a number of significant frequencies. The probable frequency of maximum emission had been found and that the associated cable and EUT configuration and mode of operation had been identified.

The bandwidth of the Receiver is set at 120 kHz.

4.4. Test Results

PASS

The test curves are shown in the following pages.



Test item: Radiation Test Polarization: Horizontal
Standard: (RE)EN 55032 Power Source: AC 230V, 50Hz
Frequency Range: 30MHz ~ 1000MHz Temp.(°C)/Hum.(%RH): 24.5(°C)/50%RH
Distance: 3m



Note: Result= Reading + Factor Over Limit=Result-Limit



Test item: Radiation Test Polarization: Vertical
Standard: (RE)EN 55032 Power Source: AC 230V, 50Hz
Frequency Range: 30MHz ~ 1000MHz Temp.(°C)/Hum.(%RH): 24.5(°C)/50%RH
Distance: 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	32.2925	54.09	-17.58	36.51	50.00	-13.49	QP			
2	45.5348	47.63	-15.13	32.50	50.00	-17.50	QP			
3	81.4970	52.64	-19.08	33.56	50.00	-16.44	QP			
4	136.4598	54.41	-21.93	32.48	50.00	-17.52	QP			
5	146.8877	55.04	-22.12	32.92	50.00	-17.08	QP			
6	167.8243	52.87	-21.23	31.64	50.00	-18.36	QP			

Note: Result= Reading + Factor Over Limit=Result-Limit



5. Radiated Emission Test (Above 1GHz)

5.1. Test Standard and Limit

Test Standard	EN 55032
---------------	----------

☒ **Limit for radiated emissions at frequencies above 1 GHz for class A equipment**

Frequency (MHz)	Distance (Meters)	Field Strengths Limit (dB μ V/m)	
		Peak	Average
1000 ~ 3000	3	76	56
3000 ~ 6000	3	80	60


Remark: The lower limit shall apply at the transition frequencies.

☐ **Limit for radiated emissions at frequencies above 1 GHz for class B equipment**

Frequency (MHz)	Distance (Meters)	Field Strengths Limit (dB μ V/m)	
		Peak	Average
1000 ~ 3000	3	70	50
3000 ~ 6000	3	74	54

Remark: The lower limit shall apply at the transition frequencies.

5.2. Test Setup



5.3. Test Procedure

The table-top EUT is placed on a non-conductive table 0.8 m above the horizontal ground reference plane. The floor-standing EUT is placed on an insulating support 0.1 m above the horizontal ground reference plane.

The EUT was set 3 m away from the receiving antenna that was mounted on a non-conductive mast. The antenna can move up and down between 1 to 4 m to find out the maximum emission level.

The turntable can rotate 360 degree to determine the position of the maximum emission level.

The initial testing identified the frequency that has the highest disturbance relative to the limit while operating the EUT in typical modes of operation and cable positions in a test setup representative of typical system configuration.

The identification of the frequency of highest emission with respect to the limit was found by investigating emissions at a number of significant frequencies. The probable frequency of maximum emission had been found and that the associated cable and EUT configuration and mode of operation had been identified.

The test receiver is set to peak and average detects function.

The bandwidth of the test receiver is set at 1MHz.

5.4. Test Results

PASS

The test curves are shown in the following pages.



Test item: Radiation Test Polarization: Horizontal
Standard: (RE)EN 55032 Power Source: AC 230V, 50Hz
Frequency Range: 1GHz ~ 6GHz Temp.(°C)/Hum.(%RH): 24.5(°C)/50%RH
Distance: 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	1253.277	71.20	-27.20	44.00	76.00	-32.00	peak			
2	1253.277	57.43	-27.20	30.23	56.00	-25.77	AVG			
3	1660.416	68.21	-26.74	41.47	76.00	-34.53	peak			
4	1660.416	54.09	-26.74	27.35	56.00	-28.65	AVG			
5	2126.188	73.00	-24.95	48.05	76.00	-27.95	peak			
6	2126.188	60.18	-24.95	35.23	56.00	-20.77	AVG			
7	2951.232	71.99	-22.63	49.36	76.00	-26.64	peak			
8	2951.232	59.37	-22.63	36.74	56.00	-19.26	AVG			
9	4261.126	69.51	-18.99	50.52	80.00	-29.48	peak			
10	4261.126	56.54	-18.99	37.55	60.00	-22.45	AVG			
11	5330.811	57.97	-16.27	41.70	80.00	-38.30	peak			
12	5330.811	40.62	-16.27	24.35	60.00	-35.65	AVG			

Note: Result=Reading + Factor Over Limit=Result - Limit



Test item: Radiation Test

Polarization:

Vertical

Standard: (RE)EN 55032

Power Source:

AC 230V, 50Hz

Frequency Range: 1GHz ~ 6GHz

Temp.(°C)/Hum.(%RH):

24.5(°C)/50%RH

Distance: 3m



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	1198.377	77.39	-27.30	50.09	76.00	-25.91	peak			
2	1198.377	66.03	-27.30	38.73	56.00	-17.27	AVG			
3	2126.188	75.02	-24.95	50.07	76.00	-25.93	peak			
4	2126.188	61.08	-24.95	36.13	56.00	-19.87	AVG			
5	2393.093	76.48	-24.43	52.05	76.00	-23.95	peak			
6	2393.093	64.66	-24.43	40.23	56.00	-15.77	AVG			
7	2786.779	71.89	-23.52	48.37	76.00	-27.63	peak			
8	2786.779	59.95	-23.52	36.43	56.00	-19.57	AVG			
9	4261.126	70.15	-18.99	51.16	80.00	-28.84	peak			
10	4261.126	56.45	-18.99	37.46	60.00	-22.54	AVG			
11	5989.259	58.65	-13.48	45.17	80.00	-34.83	peak			
12	5989.259	45.95	-13.48	32.47	60.00	-27.53	AVG			

Note: Result=Reading + Factor Over Limit=Result - Limit




6. Harmonic Current Test

6.1. Test Standard

Test Standard:	EN IEC 61000-3-2
----------------	------------------

6.2. Test Setup



6.3. Test Procedure

The table-top EUT is placed on the top of a wooden table 0.8 m above the ground (0.1 m for the floor-standing EUT) and operated to produce the maximum harmonic components under normal operating conditions for each successive harmonic component in turn. The correspondent test program of test instrument to measure the current harmonics emanated from EUT is chosen. The measure time shall be not less than the necessary for the EUT to be exercised.

6.4. Test Results

(The active input power of the EUT is less than 75W. Therefore, according to EN IEC 61000-3-2, no limits are necessary.)




7. Voltage Fluctuations & Flicker Test

7.1. Test Standard

Test Standard:

EN 61000-3-3

7.2. Test Setup



7.3. Test Procedure

The table-top EUT is placed on the top of a wooden table 0.8 m above the ground (0.1 m for the floor-standing EUT) and operated to produce the most unfavorable sequence of voltage changes under normal conditions during the flicker measurement. The observation period for short-term flicker indicator is 10 minutes and the observation period for long-term flicker indicator is 2 hours.

7.4. Test Results


PASS

The test curves are shown in the following pages.



Flicker Test Summary (Run time)

Flicker Emission IEC 61000-4-15 for 230V/50Hz



Actual Flicker (Fli):	0.00
Short-term Flicker (Pst):	0.07
Limit (Pst):	1.00
Long-term Flicker (Plt):	0.00
Limit (Plt):	0.65
Maximum Relative Volt. Change (dmax):	0.00%
Limit (dmax):	4.00%
Relative Steady-state Voltage Change (dc):	0.03%
Limit (dc):	3.00%
Tmax 3.00% (dt):	0.00ms
Limit (dt>Lim):	200ms

Flicker Emission - IEC 61000-3-3, EN 61000-3-3

Urms = 229.5 V P = 14.97 W
Irms = 0.166 A pf = 0.393

Range: 2 A
V-nom: 230 V

Test aborted, Result: PASSED

HAR-1000 EMC-Partner

Full Bar : Actual Values
Empty Bar : Maximum Values
Circles : Average Values
Blue : Current , Green : Voltage , Red : Failed

Urms = 229.5V Freq = 50.000 Range: 2 A
Irms = 0.166A Ipk = 0.967A cf = 5.824
P = 14.97W S = 38.10VA pf = 0.393

Test - Time : 10 x 1min = 10min (100 %)

LIN (Line Impedance Network) : L: 0.24ohm +j0.15ohm N: 0.16ohm +j0.10ohm

Limits : Plt : 0.65 Pst : 1.00
dmax : 4.00 % dc : 3.00 %
dtLim: 3.00 % dt>Lim: 200ms

Test aborted, Result: PASSED

	dmax [%]	dc [%]	dt>Lim [ms]
1	0.000	0.000	0.000



8.1. Test Specification

Test Standard :	EN 55035	
Basic standard :	IEC 61000-4-2: 2008	
Performance criteria:	B	
Test Level :	± 8kV (Air Discharge)	± 4kV (Contact Discharge)

The diagram illustrates the test setup for ESD immunity testing. It shows a Wall, EUT & Peripheral, ESD Generator, and various components like VCP, HCP, and GRP. Dimensions include 0.1m, 0.8m, and $\geq 1.0\text{m}$. Resistors are labeled $470\text{k}\Omega$.

- Ambient temperature: 15°C to 35°C;
- Relative humidity: 30% to 60%;
- Atmospheric pressure: 86 kPa (860 mbar) to 106 kPa (1060 mbar)

c. In the case of painted surface covering a conducting substrate, the following procedure shall be adopted: - If the coating is not declared to be an insulating coating by the equipment manufacturer, then the pointed tip of the generator shall penetrate the coating so as to make contact with the conducting substrate. - Coating declared as insulating by the manufacturer shall only be submitted to the air discharge. - The contact discharge test shall not be applied to such surfaces.



d. In the case of air discharges, the round discharge tip of the discharge electrode shall be approached as fast as possible (without causing mechanical damage) to touch the EUT. After each discharge, the ESD generator (discharge electrode) shall be removed from the EUT. The generator is then retriggered for a new single discharge. This procedure shall be repeated until the discharges are completed. In the case of an air discharge test, the discharge switch, which is used for contact discharge, shall be closed.

e. The test voltage shall be increased from the minimum to the selected test severity level, in order to determine any threshold of failure. The final test level should not exceed the product specification value in order to avoid damage to the equipment.

f. The test shall be performed with both air discharge and contact discharge. The test shall be performed with single discharges. On each pre-selected point at least 10 single discharges (in the most sensitive polarity) shall be applied. For the time interval between successive single discharges an initial value of 1 s is recommended. Longer intervals may be necessary to determine whether a system failure has occurred.

g. Ensure that the applied charge on the EUT has been dis-charged before next ESD pulse.

8.4. Test Results

PASS

Please refer to the following page.



Electrostatic Discharge Test Results

Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	Temperature:	23.2℃
Power Supply:	AC 230V, 50Hz	Humidity:	49%
Location		Kind A-Air Discharge C-Contact Discharge	Result
Air discharge: ± 2.0 kV, ± 4.0 kV, ± 8.0 kV		Contact discharge: ± 4.0 kV	
DC Port	4 points	A	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
USB Port	4 points	C	<input type="checkbox"/> A <input checked="" type="checkbox"/> B <input type="checkbox"/> C
LAN Port	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
VGA Port	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
HDMI Port	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
COM Port	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Screw	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Slot	4 points	A	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Metal	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Button	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Light	4 points	A	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
HCP	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
VCP of the front	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
VCP of the rear	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
VCP of the left	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
VCP of the right	4 points	C	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Note: N/A			




9. RF Field Strength Immunity Test

9.1. Test Specification

Test Standard:	EN 55035		
Basic standard:	IEC 61000-4-3: 2006+A1:2007+A2:2010		
Performance criteria:	A	A	A
Frequency Range:	<input checked="" type="checkbox"/> 80MHz to 1000MHz	<input checked="" type="checkbox"/> Spot frequencies	<input type="checkbox"/> Additional spot frequencies
Test level:	3 V/m	3 V/m	3 V/m
Modulation:	1kHz Sine Wave, 80%, AM Modulation		
Frequency Step:	1 % of preceding frequency value		
Polarity of Antenna:	Horizontal and Vertical		
Test Distance:	3 m		
Antenna Height:	1.5 m		
Dwell Time:	at least 0.5s		
Spot frequencies: 1800 MHz, 2600 MHz, 3500 MHz and 5000 MHz; Additional spot frequencies: 80 MHz, 120 MHz, 160 MHz, 230 MHz, 434 MHz, 460 MHz, 600 MHz, 863 MHz and 900 MHz .			

9.2. Test Setup



9.3. Test Procedure

The procedure defined in this part requires the generation of electromagnetic fields within which the test sample is placed and its operation observed. To generate fields that are useful for simulation of actual (field) conditions may require significant antenna drive power and the resultant high field strength levels. To comply with local regulations and to prevent biological hazards to the testing personnel, it is recommended that these tests be carried out in a shielded enclosure or semi-anechoic chamber.

a. The antenna is placed 3 m from the equipment. The required field strength is determined by placing the field strength meter(s) on top of or directly alongside the equipment under test and monitoring the field strength meter via a remote field strength indicator outside the enclosure while adjusting the continuous-wave to the antenna.

b. The test shall normally be performed with the generating antenna facing each side of the EUT. When equipment can be used in different orientations (i.e. vertical or horizontal) all sides shall be exposed to the field during the test. When technically justified, some EUTs can be tested by exposing fewer faces to the generating antenna. In other cases, as determined for example by the type and size of EUT or the frequencies of test, more than four azimuths may need to be exposed.

c. The polarization of the field generated by each antenna necessitates testing each selected side twice, once with the antenna positioned vertically and again with the antenna positioned horizontally.

d. The step size of the frequency is set to 1%. The dwell time at each frequency shall not be less than the time necessary for the EUT to be exercised and to be able to respond. However, the dwell time should not exceed 5 s at each of the frequencies during the scan.

9.4. Test Results

PASS

Please refer to the following page.



RF Field Strength Susceptibility Test Results

Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	Temperature:	23.9℃		
Power Supply:	AC 230V, 50Hz	Humidity:	52%		
Frequency Range	Antenna Polarity	R.F. Field Strength	Dwell Time	Azimuth	Result
80 MHz ~ 1000 MHz	H / V	3 V/m	1s	Front	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
				Rear	
				Left	
				Right	
Spot frequencies	H / V	3 V/m	1s	Front	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
				Rear	
				Left	
				Right	
Additional spot frequencies	H / V	3 V/m	1s	Front	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
				Rear	
				Left	
				Right	
Note: N/A					




10. Electrical Fast Transient/Burst Immunity Test

10.1. Test Specification


Test Standard:	EN 55035
Basic standard:	IEC 61000-4-4: 2012
Performance criteria:	B
Test Level:	<input checked="" type="checkbox"/> 1 kV, AC mains power ports
	<input type="checkbox"/> 0.5 kV, DC network power ports
	<input type="checkbox"/> 0.5 kV, Analogue/digital data ports

10.2. Test Setup

AC mains power ports and DC network power ports:



Analogue/digital data ports:



10.3. Test Procedure

The table-top EUT is placed on a table that is 0.8 m height, a ground reference plane is placed on the table, and uses 0.1 m insulation between the EUT and ground reference plane. The floor-standing EUT is placed on a ground reference plane and insulated from it by an insulating support with a thickness of 0.1 m. This reference ground plane shall project beyond the EUT by at least 0.1 m on all sides and the minimum distance between EUT and all other conductive structure, except the ground plane beneath the EUT, shall be more than 0.5 m.

All cables to the EUT shall be placed on the insulation support 0.1 m above the ground reference plane. Cables not subject to electrical fast transients shall be routed as far as possible from the cable under test to minimize the coupling between the cables.

10.4. Test Results

PASS

Please refer to the following page.



Electrical Fast Transient/Burst Test Results

Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	Temperature:	23.2℃	
Power Supply:	AC 230V, 50Hz	Humidity:	49%	
Ports	Polarity	Inject Time(s)	Test Voltage (kV)	Result
AC mains power ports	±	120 s	1.0 kV	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
DC network power ports	±	120 s	0.5 kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Analogue/digital data ports (xx Line)	±	120 s	0.5 kV	<input type="checkbox"/> A <input type="checkbox"/> B <input checked="" type="checkbox"/> C
Note: N/A				




11. Surge Immunity Test

11.1. Test Specification

Test Standard:		EN 55035
Basic standard:		IEC 61000-4-5: 2014+A1:2017
Test level	AC power port:	<input checked="" type="checkbox"/> 1 kV, Line to Line, Criterion B
		<input type="checkbox"/> 2kV, Line to Earth, Criterion B
	DC network power port:	<input type="checkbox"/> 0.5kV, Line to Reference ground, Criterion B
	Coaxial or shielded port:	<input type="checkbox"/> 0.5kV, Shield to ground, Criterion B
	Unshielded symmetrical port:	<input type="checkbox"/> 1 kV and 4 kV, lines to ground , Primary protection, Criterion C
		<input type="checkbox"/> 1 kV, lines to ground , Non primary protection, Criterion C
Number of surges		5 (for each combination of parameters)
Repetition rate		1 minute / time
Polarity:		Positive / Negative
Phase angle:		90°, 270° (Only AC mains power ports)

11.2. Test Setup



11.3. Test Procedure

Table-top EUT is placed on a table of 0.8 m heights above a metal ground reference plane. Floor standing EUT is placed on a ground reference plane and insulated from it by an insulating support with a thickness of 0.1 m. The length of the power cord between the EUT and the coupling/decoupling network is not more than 2 m, and the length of the interconnection line between the EUT and the coupling/decoupling network is not more than 2 m. The tests were done at repetition rate 1 per minute.

11.4. Test Results

PASS

Please refer to the following page.

Shenzhen Anbotech Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86) 0755-26066440 Fax: (86) 0755-26014772 Email: service@anbotech.com

Code: AB-EMC-02-c



Hotline

400-003-0500

www.anbotech.com.cn



Surge Immunity Test Results

Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	Temperature :	23.2℃		
Power Supply :	AC 230V, 50Hz	Humidity :	49%		
Location	Polarity	Phase Angle	Number of Pulse	Pulse Voltage (kV)	Result
<input checked="" type="checkbox"/> AC power port (Waveform: 1.2 us / 50 us (8 us / 20us))					
L-N	+	<input type="checkbox"/> 0° <input checked="" type="checkbox"/> 90° <input type="checkbox"/> 180° <input type="checkbox"/> 270°	5	0.5, 1kV	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
	-	<input type="checkbox"/> 0° <input type="checkbox"/> 90° <input type="checkbox"/> 180° <input checked="" type="checkbox"/> 270°	5	0.5, 1kV	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
L-GND	+	<input type="checkbox"/> 0° <input checked="" type="checkbox"/> 90° <input type="checkbox"/> 180° <input type="checkbox"/> 270°	5	0.5, 1, 2kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
	-	<input type="checkbox"/> 0° <input type="checkbox"/> 90° <input type="checkbox"/> 180° <input checked="" type="checkbox"/> 270°	5	0.5, 1, 2kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
N-GND	-	<input type="checkbox"/> 0° <input checked="" type="checkbox"/> 90° <input type="checkbox"/> 180° <input type="checkbox"/> 270°	5	0.5, 1, 2kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
	+	<input type="checkbox"/> 0° <input type="checkbox"/> 90° <input type="checkbox"/> 180° <input checked="" type="checkbox"/> 270°	5	0.5, 1, 2kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
<input type="checkbox"/> DC network power ports (Waveform: 1.2 us / 50 us (8 us / 20us))					
Line to Reference ground	+	/	5	0.5kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
	-	/	5	0.5kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
<input type="checkbox"/> Analogue/digital data ports (Waveform: 10 us / 700 us (5 us / 320us)) : xx lines(注明测试线缆, 如没有删掉黄色部分)					
Lines to ground	+	/	5	0.5, 1kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
	-	/	5	0.5, 1kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
<input type="checkbox"/> Analogue/digital data ports (Waveform: 10 us / 700 us (5 us / 320us)) : xx lines(注明测试线缆, 如没有删掉黄色部分)					
Lines to ground	+	/	5	0.5, 1, 2, 4kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
	-	/	5	0.5, 1, 2, 4kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
<input type="checkbox"/> Analogue/digital data ports (Waveform: 1.2 us / 50 us (8 us / 20us)): Coaxial or shielded lines					
Shield to ground	+	/	5	0.5kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
	-	/	5	0.5kV	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Note: N/A					




12. Injected Currents Susceptibility Test

12.1. Test Specification


Test Standard:	EN 55035		
Basic standard:	IEC 61000-4-6: 2013		
Performance criteria:	A		
Frequency range:	0.15M to 10MHz	10M to 30MHz	30M to 80MHz
Test level:	3V	3V to 1V	1V
Modulation:	AM 80%, 1kHz sine-wave		
Frequency Step:	1% of fundamental		

12.2. Test Setup

CDN injection:



Clamp injection:



12.3. Test Procedure

- a. The EUT and peripheral are placed on an insulating support of 0.1 m height above a ground reference plan. The distance between EUT and CDN is 0.1 m to 0.3 m. All cables exiting the EUT are supported at a height of at least 30 mm above the ground reference plan.
- b. The frequency range is swept from 150 kHz to 80MHz, with the signal 80% amplitude modulated with a 1 kHz sine wave. The rate of sweep did not exceed 1.5×10^{-3} decade/s. The frequency range is swept incrementally. The step size was 1% of fundamental from 0.15MHz to 80MHz.
- c. The dwell time at each frequency isn't less than the time necessary for the EUT to be able to respond.

12.4. Test Results**PASS**

Please refer to the following page.



Injected Currents Susceptibility Test Results

Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	Temperature:	23℃
Power Supply:	AC 230V, 50Hz	Humidity:	48%
Frequency Range (MHz)	Injected Position	Strength (Un-modulated)	Result
0.15 ~ 10	AC Mains	3V	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
10 ~ 30	AC Mains	3V to 1V	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
30 ~ 80	AC Mains	1V	<input checked="" type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
0.15 ~ 10		3V	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
10 ~ 30		3V to 1V	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
30 ~ 80		1V	<input type="checkbox"/> A <input type="checkbox"/> B <input type="checkbox"/> C
Note: N/A			




13. Power Frequency Magnetic Field Immunity Test

13.1. Test Specification

Test Standard:	EN 55035
Basic Standard	IEC 61000-4-8: 2009
Performance criteria	A
Test level	1A/m

13.2. Test Setup



13.3. Test Procedure

Table-top EUT is placed on a table that is 0.8 m height. Floor standing EUT is placed on a ground reference plane and insulated from it by an insulating support with a thickness of 0.1 m.

The EUT is placed in the middle of an induction coil. The proximity method is used when the EUT does not fit into the standard inductive coil

13.4. Test Results

Not applicable




14. Voltage Dips and Interruptions Immunity Test

14.1. Test Specification

Test Standard:	EN 55035
Basic standard:	IEC 61000-4-11: 2020
Test level:	<input checked="" type="checkbox"/> 0%, 0.5 period, Criterion B
	<input checked="" type="checkbox"/> 70%, 25 periods for 50Hz, Criteria C
	<input checked="" type="checkbox"/> 0%, 250 periods for 50Hz, Criteria C
	<input type="checkbox"/> 70%, 30 periods for 60Hz, Criteria C
	<input type="checkbox"/> 0%, 300 periods for 60Hz, Criteria C

14.2. Test Setup



14.3. Test Procedure

a. Where the equipment has a rated voltage the following shall apply:

- If the voltage range does not exceed 20% of the lower voltage specified for the rated voltage range, a single voltage within that range may be specified as a basis for test level specification.
- In all other cases, the test procedure shall be applied for both the lowest and highest voltages declared in the voltage range.

b. Test Conditions

- Select operated voltage and frequency of EUT - Test of interval: 10 sec.
- Level and duration: Sequence of 3 dips/interrupts.
- Voltage rise (and fall) time: 1.5 μ s.

c. Changes to occur at 0 degree crossover point of the voltage waveform.

14.4. Test Results

PASS

Please refer to the following page.



Voltage Dips and Interruptions Test Results

Test Result:	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	Temperature :	23.2℃
Power Supply :	AC 230V, 50Hz	Humidity :	49%
Test Level % UT	Voltage Dips & Short Interruptions % UT	Duration (in periods)	Result
0	100	0.5P	<input type="checkbox"/> A <input checked="" type="checkbox"/> B <input type="checkbox"/> C
70	30	25P	<input type="checkbox"/> A <input type="checkbox"/> B <input checked="" type="checkbox"/> C
Test Level % UT	Voltage Dips & Short Interruptions % UT	Duration (in periods)	Result
0	100	250P	<input type="checkbox"/> A <input type="checkbox"/> B <input checked="" type="checkbox"/> C
Note: N/A			



APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Power Line Conducted Emission Test




Photo of Asymmetric Mode Conducted Emission at Telecom Port




Photo of Radiated Emission Test (Below 1 GHz)




Photo of Radiated Emission Test (Above 1GHz)



Photo of Harmonic Current And Flicker Test




Photo of Electrostatic Discharge Immunity Test




Photo of RF Field Strength Immunity Test




Photo of Electrical Fast Transient/Burst Immunity Test



Photo of Surge Immunity Test



Photo of Injected Currents Susceptibility Test






Photo of Voltage Dips and Interruptions Immunity Test



APPENDIX II -- EXTERNAL PHOTOGRAPH





APPENDIX III -- INTERNAL PHOTOGRAPH



CE Label

1. The CE conformity marking must consist of the initials 'CE' taking the following form:

If the CE marking is reduced or enlarged, the proportions given in the above graduated drawing must be respected.

2. The CE marking must have a height of at least 5 mm except where this is not possible on account of the nature of the apparatus.
3. The CE marking must be affixed to the product or to its data plate. Additionally it must be affixed to the packaging, if any, and to the accompanying documents.
4. The CE marking must be affixed visibly, legibly and indelibly.

It must have the same height as the initials 'CE'.

----- End of Report -----

